

On-the-Fly Repair Of A Computer

This continuation-in-part claims priority to pending application Serial No. 09/862,898, filed on May 21, 2001, with Atty. Docket No. A-70543/RMA/LM.

U.S. Patent Application No. 09/862,898 is incorporated herein by reference.

The following invention provides an apparatus and method of supporting the backup and recovery of a computing device. The computing device will typically include both a user computing environment and a supporting environment which enhances the stability and functionality of the user computing environment.

Processes

In one embodiment, a plurality of computing processes may be utilized to enable the On-the-Fly invention. Here, individual computing processes may monitor, track, predict the stability, backup, restore, or recover attributes within the user computing environment. The attributes may be software specific, data specific, operating system specific, or any combination. Utilization of the plurality of computing processes can facilitate the normal operation of the user computing environment. In one embodiment the user computing environment may be stabilized without user intervention such as requiring the user to shut-down, restart, logging off, logging on, or terminating applications. In one embodiment the supporting environment may have a capability interacting with the user computing environment. In one embodiment the supporting environment may be capable of initiating or causing the user computing environment to shut-down, restart, logging off, logging on, or terminating applications.

Different computing systems

In one embodiment the user computing environment and the supporting environment function in different computing systems. The two computing systems may reside in a common box. The user computing system may consist of data storage devices, RAM, processor, video card, and other attributes known in the art to facilitate a computing system. The supporting computing system may consist of a master template data storage device, RAM, processor, and other attributes known in the art to facilitate a computing system. In one embodiment, the data storage devices may be linked as needed to perform repairs. Such as, the need to copy data from the support environment to the user environment.

Snap-Shot of data

In one embodiment, the present invention takes a snap-shot of the user computing environment. This snap-shot may subsequently be utilized to restore, analyze, or enhance the stability of the user environment. The snap-shot may include a stable image of the operating system, software

applications, or user data. The snap-shot may contain an idealized or stable version of a disk drive utilized by the user environment, or a subset of the disk drive such as an individual partition. The snap-shot may also include an idealized version or image of the user system RAM, user system disk drive, user system partition image, memory of the video card, or any other memory stored or utilized in the user computing environment. These snapshots may be stored in the associated support environment data storage device.

Monitoring

The supporting environment may monitor the user environment. The monitoring may include monitoring of processes running or enabled within the user environment. The monitoring may include monitoring both the utilization of the data storage device, data contained on the data storage device, and other aspect necessary for the normal operation of the user environment. This monitoring may facilitate identifying undesired changes, potential problems and also potential solutions. The supporting system may detect a freeze or other undesirable change within the user environment.

Recovery

When an undesirable change is detected in the user environment, the supporting environment may attempt to recover or restore or repair the user environment. The supporting system may be capable of re-enabling the user environment in a number of ways, such as resetting the keyboard in the event the keyboard locks the communication of keystrokes to the user environment. Further recovery of the user environment may be supported by reset connections such as describe by "Freezebuster", reset and clear devices as needed, replace defective software components as needed, and/or switch hardware components and/or devices as needed. The supporting environment and or supporting system may copy all or part of the data from one or more of the idealized snapshots mentioned above. These snapshots may be copied into their respective devices and/or locations.

Application Configuration

Another embodiment supports an ability to run two or more different programs at the same time on one computing system where the data and applications may be isolated from one another but may share output and/or input devices. In one embodiment, the applications may be isolated by executing the applications in a separate address space. The applications and data may be further isolated by utilizing two separated data storage devices. In order to safely send a command from one isolated data storage device to the other isolated data storage device the following may be utilized. In one embodiment, when an icon on the desktop icon is clicked the following may occur. The icon may execute a command that would launch a specific application on the other isolated data storage device. This may be accomplished by a shared ASIC that sends the command to the other isolated data storage device.

Another embodiment involves isolation of data with merged display. In this embodiment

two user environments can be separated for the purposed of isolating data. For the Anti-Hacker System: A hard drive that does not contain "sensitive" data could be isolated and attached to a network. A second hard drive, may or may not be attached to the other hard drive (in any way), could be utilized for "sensitive" user data, but have no exposure to the network because it is "isolated" by a means of switching. The video signals associated with the data coming from these two hard drives could then be "merged" onto the same screen. In other words, all of the computing would be happening within isolated "secure zones" within a single computer but would not appear so to the user. Another example: the anti-virus system could use this method to isolate potentially infectious data.

Application Output

Applications may have its output displayed on the same screen alongside and/or superimposed upon the same screen with other applications and data that were being "computed" separately. Both computing processes may be separated but may then be "merged" together on the screen, and/or overlaid one another on the same screen. In one embodiment, this may be achieved by using multiple video cards. This concept can be applied for example to the Repair System, Multi User, Anti-Hacker, anti-theft and Anti-Virus.

In another embodiment both the user computing environment and the supporting environment will reside on a single computer system. A snap-shot of the operational user environment will be taken. The snap-shot will be associated with the supporting environment. Processes associated with the supporting environment will monitor the activities and status of the user computing environment. The monitoring function will become aware of any degraded performance of the user computing environment, such as a system freeze up. The monitoring function notifies the supporting environment of any degraded performance. The supporting environment will perform any recovery action as necessary to recover or restore the user environment. Recovery may include utilizing the snap-shot to recover or restore the user environment. An entire user disk may be restored. A specific application or software package may be restored, or particular files.

What is claimed is:

1. A computer system that repairs itself on the fly.